

CPOLYTECH EXTREME

SEVERE CORROSION, EROSION, & CHEMICAL ATTACK ENVIRONMENTS

E 2322

Is a 100% solids, sprayable ceramic-reinforced, dual-component liquid polymer composite formulated with a modified phenol novolac epoxy resin and fine ceramic fillers. It is specifically designed to provide excellent laminar flow and protection against severe corrosion, erosion, and chemical attack, making it also ideal for continued immersion environments.

MAXIMIZING YOUR BENEFITS

SPRAYABLE

A simpler and faster way to protect your asset

FINE CERAMIC FILLERS

Ideal for severe fine particulate wear

OUTSTANDING CHEMICAL AND ABRASION RESISTANCE

Making it an excellent choice for extending the life of your assets

HIGH GLOSS, LOW DRAG SURFACE

Reducing the amount of energy required to operate the equipment

MAXIMIZING YOUR APPLICATIONS

- Storage tanks
- Secondary containments
- Pumps & Valves
- Heat exchangers
- Slurry systems

- **Pipelines**
- Immersion applications
- Chemical attack
- High wear & abrasion
- Mixing vessels

CURING TIMES (25°C)		
Dry-to-touch	3.5 hrs	
No loading or immersion	4 hrs	
Machining or light loading	20 hrs	
Full mechanical load	48 hrs	
Full chemical	270 hrs	
Dry Film Thickness	250 μm	

THEORETICAL COVERAGE @ 250 μm		WINDOW RECOAT	
1 kg covers	2,86 m ²	Minimum	3.5 hrs
5 kg covers	14,30 m ²	Maximum	24 hrs
PACKI	NG	DA	TA
DGC 2232.01	1 kg	Ratio Volume	4:1
DGC 2232.05	5 kg	Ratio Weight	5.8:1
DGC 2232.20	20 kg	Working time	35 mins
Shelf Life	24 months	Density A + B	1.40

PROPERTIES		
Adhesion ASTM D4541	27 Mpa >4600 psi	
Abrasion resistance ASTM D4060	26 mm ³ CS17 (dry)	
Compressive Strength ASTM D695	59 Mpa >9200 psi	
Hardness (Shore D) ASTM D2240	83	
Tensile Strength ASTM D638	26 Mpa >6500 psi	
Flexural Strength ASTM D790	30 Mpa >4300 psi	
Impact Resistance ASTM D256	4.0 kJ/m ²	
Temperature Resistance ASTM D 3418	130 °C 266 °F	
Heat Resistance	200 °C 392 °F	

DICKINSON COPPERBELT SERVICES LTD DGC WORKFORCE SOLUTIONS

- T +260 76 183 2470
- +260 96 552 4350 +260 96 146 6000
- contactus@dgc-africa.com

Plot 2394, Freedom Way, Mufulira

DGC AFRICA (DRC) S.A.S SARENS DRC S.A.S. (DRC)

- +243 89 964 9493
- +243 89 342 9009
- +243 89 403 1340
- contactus@dgc-africa.com

199 Avenue Mubanzo Quartier Golf Malela, Commune Lubumbashi, Province du Haut-Katanga

DGC MADAGASCAR SA

- T +27 (0) 82 319 8005
- +27 (0) 79 016 9868
- +261 32 112 2122 contactus@dgc-africa.com

Lot lvx 30 Bis Ankazomanga rue Dr Raseta Antananarivo, 101 Madagascar

